

### CONSUMABLES

Our material range has been specially developed for engraving and cutting. "Surface" or "reverse" engraving, laser marking or cutter engraving, also compatible with digital printing, all our ranges of plastic, metal or stratified materials are available in a spectrum of colours, thicknesses, and finishes.



Laser materials

Rotary materials



Engravables



**SERVICE & SUPPORT** 



Training

Technical Support

With our direct presence in over 50 countries, we always have a marking and engraving expert close to you to

bring their expertise and know-how in qualifying your application, installing your equipment and training your

Maintenance

to provide you with the offer, best



Signage



Cutters & Inserts

**Engraving supplies** 

## THE EXPRESSION OF THINGS

able to express themselves. With the CAD software and Consumables creation to production and service cutting-edge technologies that we with support all over the world. master for permanent marking and engraving, we are giving this power to objects.

Laser, mechanical engraving, scribing and dot peen: we are the only ones to pioneer and master all these types of marking.

Humans have a unique quality: to be We are a manufacturer of machines, We know the entire chain, from

suited to your needs. The result of the integration of Gravotech was born in 2008 from pioneering technologies, we are the merger of Gravograph, Technifor constantly exploring new solutions and Type3 and unified under one to innovate and shape the future of brand in 2021. the Expression of Things.

Gravotech in video



### SOFTWARE

Our engraving and cutting expertise lead us to build our own software. Create your engraving and cutting paths, pilot your machines, design your 3D jewelry, Anything is possible!



ABC software is the easiest engraving software for

Gravotech laser and rotary machines. Engrave in

only 3 simple steps, from a computer or a tablet!

3 D E S I G N

Cutting edge 3D software for jewelry design that

will keep your business ahead.



One-of-a-kind piloting software for Gravotech laser

and rotary engraving machines.

TYPE EDIT

For over 30 years, TYPE EDIT is the complete CAD/CAM software solution. Taking your ideas

and drawings, through design and machining to

production





LASERTRACE

Lasertrace is the Gravotech industrial software for traceability and identification. Various functions are available in a simple and friendly interface, for





TYPE3-CAA is the only add-on available in CATIA® environment for text creation and mapping.





info@regros.si 01 517 42 00 www.regros.si

REGROS TRGOVINA IN INŽINIRING d.o.o. Ferberjeva ulica 4 1000 Ljubljana Slovenija

Sledite nam na: (D) (O)









15200



IS400 /IS400 VOLUME



ISX000



LS100

cutting, and personalization



LS100EX



LS900



FIBER



HYBRID



GREEN

CO2

Small signage and identification	
engraving machine	

One of a kind metal engraving machine

The large format CNC engraving machine

LASER

LASER

STATIONS

**TABLES** 

CO2 laser engraver for signage, creative

The signage and small series laser engraving machine

The large laser engraver that can do everything

Integrated laser marking system for metal and plastic parts

INTEGRABLE

LASER

**MARKERS** 

versatility, high quality and high speed to meet all your marking needs

Integrated laser marking system to mark highly reflective materials and sensitive plastic materials

High-speed laser engraver: the best to mark organic materials and coated surfaces

Application scope	Ш	IIII	Ш	Application scope	Ш	III	Ш	Application scope	II	II	II	II
Technology	Rotary, diamond dragging	Rotary, diamond dragging	Rotary, diamond dragging	Laser source	CO2	CO2, Fiber	CO2, Fiber, Edge	Wavelength	1 064 nm	1 064 nm	532 nm	10 600 nm
Max. marking area (L x H)	225 x 80 mm (9 x 3")	305 x 210 mm (12 x 8")	IS6000: 610 x 410 mm (24 x 16") IS7000: 610 x 815 mm (24 x 32") IS8000: 610 x 1220 mm (24 x 4")	Power (W)	25 - 30 - 40 - 60	<b>CO2:</b> 25 - 30 - 40 - 60 <b>CO2 Energy:</b> 25 <b>Fiber:</b> 20 - 30	CO2: 40 - 60 - 80 Fiber: 20 - 30 - 50 Edge: (CO2: 40 / Fiber: 20 - 30 - 50)	Power	Fiber: 20 - 30 - 50 W Fiber Energy: 20 - 30 W	10 - 20 W	5 - 10 W	30 W
		90 W	90 - 200 W	Max. marking area (L x H)	460 x 305 mm (18 x 12")	610 x 305 mm (24 x 12")	610 x 610 mm (24 x 24")	Process automation		Industrial Ethernet Networks	PROFINET / ETHERNET IP	
Spindle power	20 W	(optional spindle: 150 W)	(optional spindle: 150, 750, 1k W)	Lenses (in)	1.5 - 2.0 - 2.5 - 3.0 - 3.5 - 4.0	1.5 - 2.0 - 2.5 - 3.0 - 3.5 - 4.0	1.5 - 2.0 - 2.5 - 3.0 - 3.5 - 4.0	Embedded intelligence	A	utonomous / Programmable by PLC / No	PC required / Traceability Management	
Max. object height	30 mm (1.2")	<b>IS400:</b> 105 mm (4") <b>IS400 Volume:</b> 400 mm (15.75")	80 mm (3")	Max. object height	145 mm (5.7")	145 mm (5.7")	250 mm (9.8")	Laser classification	Class 4 Laser syste	m, possibility to switch in Class 1 for inte	gration on a station or equipped with Mir	ni Inline module.
									MINI-IN	LINE		



The iconic pantograph by Gravotech



CNC

**TABLES** 

STATION



M10 JEWEL

Compact ring and bracelet

engraving machine



M 2 0 X

Custom engraving for all kind

of purposes, from jewelry and

perfume to small industrial signage



M40/M40GIFT

Multi-purpose rotary engraving machine for signage and gifts



Small laser engraving station

W E L A S E TM



L W 2

Fully automated laser marking station



LW3

Fully automated high volume

industrial laser station



XF510 p



XF510 m The precise and consistent electromagnetic dot peen marking machine



XF530 p/m Deep and indelible

The fastest pneumatic dot peen marking machine on the market	dot peen marking machine	dot peen marking
T	1	T

Application scope	ll ll	I	IIII	III	Application scope	II .	III	III	Application scope	I	I I	I
Technology	Rotary, scribing	Scribing	Rotary, scribing	Rotary, scribing	Laser source	Fiber, Hybrid, Green, CO2	Fiber, Hybrid, Green	Fiber, Hybrid, Green	Technology	Dot peen Pneumatic	Dot peen Electromagnetic	Dot peen Pneumatic or Electron
Max. marking area (L x H)	250 x 140 mm (9.9 x 5.5")	-	100 x 100 mm (4 x 4")	305 x 210 mm (12 x 8")	Use rate	Adapted for small to medium batches	Fully automatic Adapted for high use rate	Fully automatic Adapted for high production rates and large parts	Main advantage	Speed	2D codes	Deep marking
Spindle power	50 W	-	30 W	30 W	Max. marking area (L x I)	110 x 110 mm (4.3 x 4.3")	Up to 205 x 205 mm (8 x 8")	Up to 875 x 300 mm (34 x 12")	May modified and II v. III	<b>Cp:</b> 50 × 20 mm (2 × 0.8"),	<b>cm:</b> 50 × 20 mm (2 × 0.8"),	200 x 50 mm (7.9 x 2")
Max. object height	50 mm (2")	ø 12.5 - 80 mm (0.5 x 3.15")	100 mm (4")	110 mm (4.")	Max. object height	<b>Fiber, Hybrid, Green:</b> 100 mm (4") <b>CO2:</b> 180 mm (7")	Up to 322 mm (12.7")	Up to 628 mm (24.72")	Max. marking area (L x H)	Sp: 100 x 80 mm (4 x 3.15"),       Sm: 100 x 80 mm (4 x 3.15"),         Dp: 200 x 80 mm (7.9 x 3.15")       Dm: 200 x 80 mm (7.9 x 3.15")	200 x 30 11111 (7.9 x 2 )	
Dimensions (L x W x H)	580 x 510 x 280 mm (22.8 x 20 x 1")	230 x 293 x 290 mm (9 x 11.5 x 11.4")	368 x 350 x 363 mm (without screen) (14.5 x 13.8 x 14.3")	550 x 510 x 320 mm (27.7 x 20 x 12.6")	Max. object weigth	3 kg (6.6 lbs)	25 kg (55 lbs)	50 kg (110.23 lbs)	Material hardness (HRC)	< 62	< 62	< 62

## APPLICATIONS OF ENGRAVING, MARKING AND CUTTING

Look around you and you'll notice that most objects around you are marked, engraved or customized. Find them and you'll find Gravotech!















**DOT PEEN** 

STATION

Technology

Marking area max. (L x H)

Z axis stroke Z axis type



	Benchtop dot peen marking station
ope	T
	Dot peen pneumatic or electromagnectic
	Integrated traceability software with color touchscreen

100 x 120 mm (4 x 4.7")

300 mm (11.8")

Manual or motorized & programmable

# Want to know more?



INTEGRABLE SCRIBING

**INTEGRABLE** DOT PEEN



XF510r



The quiet metal marking machine

The VIN scribing marking machine

Application scope	I I	I .
Technology	Scribing	Scribing
Main advantage	Quiet	Deep marking
Max. marking area (L x H)	<b>Cr:</b> 40 × 50 mm (1.6 × 2"), <b>Sr:</b> 80 × 50 mm (3.15 × 2"), <b>Dr:</b> 160 × 50 mm (6.3 × 2")	120 x 40 mm (4.72 x 1.6")
Material hardness (HRC)	< 62	< 62